## **AMENDMENTS TO THE SPECIFICATION:**

Please replace the paragraph beginning on page 4, line 16 and ending on page 4, line 26 with the following amended paragraph.

Some embodiments also include means for transmitting a first PSMM\_Request message from a first cell site to the user equipment of the calling party, means for transmitting a first response to the first PSM message PSMM\_Request message, means for determining a first delay from the first response, means for transmitting a second PSMM\_Request message from a second cell site to the user equipment of the calling party, means for transmitting a second response to the second PSM message PSMM\_Request message, means for determining a second delay from the second response, means for transmitting a third PSMM\_Request message from a third cell site to the user equipment of the calling party, means for transmitting a third response to the third PSM message PSMM\_Request message, means for determining a third delay from the third response, and means for determining a relative position of the user equipment of the calling party to the first, second and third cell sites based on the first, second and third delays.

Please replace the paragraph beginning on page 4, line 27 and ending on page 4, line 31 with the following amended paragraph.

Some embodiments include means for transmitting a plurality of PSMM\_Request messages from a plurality of cell sites to the user equipment of the calling party, means for transmitting a plurality of responses to the plurality of PSM messages PSMM\_Request messages, means for determining a plurality of delays from the plurality of responses, and means for determining a relative position of the user equipment of the calling party to the plurality of cell sites from the plurality of delays.

Please replace the paragraph beginning on page 11, line 8 and ending on page 11, line 19 with the following amended paragraph.

Alternatively, if the description subscription feature determiner 418 does not provide an indication as to whether or not the user equipment of the calling party is GPS enabled the GPS coordinate determiner 422 may generate a query 242 as to whether

or not the user equipment of the calling party can provide GPS coordinates. The GPS query 242 may be transmitted to the subscriber database 234 through the network interface and intervening network 442. Alternatively, the GPS query 242 may be directed to the user equipment of the calling party. (e.g. 210, 310) via the network interface 438, network 442 and a serving base station (e.g. 218). If a response to the query indicates that the user equipment of the calling party is GPS enabled, the GPS coordinate determiner 422 generates and transmits a GPS location request message 250 as described above. If no response is received or if the response indicates that the user equipment of the calling party is not GPS enabled, the GPS coordinate determiner 422 so informs the cellular triangulator 426.